

1 **TITLE OF INVENTION**

2
3 STORM SHUTTER SYSTEM

4
5 **CROSS REFERENCES TO RELATED APPLICATIONS**

6
7 None

8
9 **STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH**

10
11 No federal research money was used in the development of this
12
13 invention.

14
15 **REFERENCE TO APPENDIX**

16
17 No appendix accompanies this application

18
19 **BACKGROUND OF THE INVENTION**

20
21 A person's largest investment during a lifetime is usually his
22
23 or her home. Great care is taken to select the location of the
24
25 home, the layout of the home and the parts to a home. Because
26
27 of this concern the homeowner spends many hours and much money
28
29 maintaining and beautifying his or her home.

30
31 The present invention is used to protect windows of a home or a
32
33 business during periods of inclement weather by using the screen
34
35 track of the existing window in the home. In the construction
36
37 of homes or businesses windows are an integral part of the
38
39 construction. Most of the windows are equipped with screens.
40
41 The purpose of the screen is to allow the owner to open the
42
43 window and prevent the entry of foreign objects.

44
45 The window with a screen is either a half screen or a full
46
47 screen. The choice of whether to have a full or half screen is
48
49 made by the property owner. Regardless of the choice the screen
50

1 will fit securely within the screen track. This allows the
2
3 screen to remain in place during normal operation of the window.
4
5 This device takes advantage of this existing track. The present
6
7 device does not require modification of the existing window or
8
9 window frame. It also does not require any modification to the
10
11 existing exterior structure of the building.

12
13 Another advantage of this device is the ease of installation and
14
15 removal as well as the relatively low cost to the homeowner.

16
17 Additionally, this is not a permanent addition to the home and
18
19 the device itself can be made aesthetically pleasing for the
20
21 homeowner.

22
23 In the half screen window the invention, which is installed on
24
25 the outside of the building, is inserted into the screen track.

26
27 The device has two separate bars on opposite sides of the device
28
29 to enable a secure fit within the screen track. One bar, which
30
31 is mounted permanently to one side of the device, would give
32
33 sufficient width and length to cover approximately 80% to 90% of
34
35 the existing screen track. On the opposite end but on the same
36
37 side of the permanent mounted side is an identical bar. Slots
38
39 are provided to adjust the "fit" of the device to the window and
40
41 tighten the device to the window for a secure fit.

42
43 In the full screen window, the device would extend from the top
44
45 of the window to the bottom of the window. In the half screen
46
47 window the device would only extend the length of the screen
48
49 track. In the half screen window molding would be installed to
50

1 make it aesthetically pleasing for the homeowner. The molding
2
3 would cover the entire window. The central idea however, would
4
5 not be changed by the addition of the molding for any particular
6
7 installation. If molding is used it would extend the full
8
9 length of the window frame and attach to the outside of the
10
11 window frame through the use of epoxy or screws.

12
13 In the case of the half screen the clamping device would be
14
15 inserted into the existing screen track of the window and the
16
17 molding would cover the remainder of the outside of the window.
18
19 The molding would rest against the window frame of the existing
20
21 window and cover the entire window surface. In this example the
22
23 lower half of the device would use the screen track for the
24
25 bottom half of the invention and the upper part of the device
26
27 would rest flush against the window frame. The upper part would
28
29 be secured to the window frame by epoxy or screws.

30
31 In the window that has a full screen the device would be
32
33 installed in the screen track and be "clamped" on the existing
34
35 frame. In this example no epoxy or screws would be necessary.
36
37 This device could also be used on any type window (bay,
38
39 casement, half screen, or full screen) in use today. The choice
40
41 of material that is used to form the barrier between the weather
42
43 and the window could be a variety of material including hard
44
45 plastic, polycarbonate or laminates to name just a few.

46
47 An advantage to this device is the easy installation using the
48
49 existing fit of the window to install this device. It is not
50

1 altering, in any way, the window nor does the homeowner have to
2
3 drill or anchor this particular device to the brick stucco or
4
5 wood on the outside of the home.

6
7 Untightening the fastening devices and sliding the bar over
8
9 accomplishes the removal of the device.

10
11 The choice of material in manufacturing this particular device
12
13 will depend upon the specific location. It must be able to
14
15 withstand high force winds and objects, which may strike the
16
17 outside of the device. The choice of material is not
18
19 significant other than the fact that it must be durable and
20
21 resistant to inclement weather.

22 23 **BRIEF SUMMARY OF THE INVENTION**

24
25 This device uses the existing screen track of a window and two
26
27 bars, which can be tightened so that the fit of the window is
28
29 secure against the window. Because it uses the existing
30
31 equipment of the window modifications do not need to be made to
32
33 the window. It does not alter the window nor does it detract
34
35 from the aesthetics of the home.

36
37 The device is not meant to be a permanent addition to the home
38
39 but merely is installed or removed in the event of inclement
40
41 weather.

42
43 It would be relatively easy to manufacture using existing
44
45 products.

46
47 The invention itself contains a board, which has predrilled
48
49 holes on one side and a bar on the opposite side of the
50

1 | predrilled holes. This is fastened with either bolts or wing
2 |
3 | nuts. This part of the invention is permanently fixed in one
4 |
5 | position.
6 |

7 | On the opposite side of the device is an identical bar. It is
8 |
9 | also attached in the same manner. However, on this side slots
10 |
11 | have been added. These slots allow the bar to move in a lateral
12 |
13 | or side-to-side fashion from one side to the other at a distance
14 |
15 | of approximately three inches. The slots will allow the user to
16 |
17 | "custom fit" the device to an existing window. The slots also
18 |
19 | insure that the fit will be a secure fit.
20 |

21 | The device itself will be custom fit to the window and will be
22 |
23 | tightened according to tightening bolts or wing nuts on the side
24 |
25 | with the slots.
26 |

27 | In the event that a half screen window is involved molding,
28 |
29 | which would be attached to the device, is also added to protect
30 |
31 | the window while using only the half screen. This molding would
32 |
33 | cover the part of the window that could not be covered by the
34 |
35 | window with the half screen track and is attached to the
36 |
37 | existing window frame using epoxy or screws.
38 |

39 | In the event that the window has a full screen the device would
40 |
41 | extend the entire length of the window. In this case no molding
42 |
43 | would be used and no attachment to the outside of the window
44 |
45 | frame would be necessary.
46 |

47 | The device could be used on any type window and would be easy to
48 |
49 | install and remove. The choice of materials would depend on a
50 |

1 particular manufacturer and their preference. The requirements
2
3 for the choice of materials are durability and strength.
4

5 **BRIEF DESCRIPTION OF THE DRAWINGS**

6
7 The invention is further described in the accompanying drawings:
8

9 Figure 1 is an exploded view of the invention.
10

11 Figure 2 is a front view of the invention.
12

13 Figure 3 is a back view of the invention.
14

15 Figure 4 is a right side view of the invention.
16

17 Figure 5 is a left side view of the invention.
18

19 Figure 6 is a perspective view of the invention and indicates
20
21 how the invention will be installed in a window.
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50

DETAILED DESCRIPTION

This invention is a piece of plywood, formica or other hard surface (100). As depicted in figure 1, the device has two bars (200, 300), which are identical but are placed on opposite sides of the device, near the outside edges of the device. One of the bars (200) is inserted through a series of holes and is attached with washers and nuts. This side of the device will remain fixed in position as the invention is used.

The other bar (300) slides from side to side by use of predrilled slots. The slots (400) have been installed so that this bar can move laterally along the surface of the device.

The washers and wing nuts help attach this particular bar to the device. The wing nuts allow the bar to be moved from side to side to accommodate particular windows. As depicted in Figure 1, the bars are of identical length and are made either of aluminum or stainless steel or other similar durable material.

The choice of material in constructing the invention is not relevant, except to the extent that they must be able to withstand high force winds and objects being thrown into them in order to protect the window. According to Figure 6, the device (200, 300) is placed within a screen track of a window. It is anticipated that this device will completely cover the window once it is properly installed on a full track screen window. On a half-track screen window it is anticipated that this device will cover one half and there will be additional molding, which

1 is attached to cover the additional one half of the window.

2
3 Again, choice of material is not important, except to the extent
4
5 that it must be durable enough to withstand high winds and/or
6
7 objects being thrown onto the surface.

8
9 Wing nuts have been installed on the device as depicted in
10
11 Figure 2, to be able to loosen the bar to be able to slide it
12
13 from side to side as the device is used.